

PRE-O800-IB-VR8

OSFP800, VR8, 850nm, 800GE/InfiniBand, 50m,
MMF/MPO16-APC, C-Temp, DDM



Product Features:

- VCSEL Transmitters
- 50m Reach over MMF
- MPO-16 APC optical connector
- < 16 W Power Consumption
- Commercial Temperature Rated
- Digital Diagnostic Monitoring (DDM)



Product Applications:

- 1x 800GBASE-VR8 Ethernet
- 2x 400GBASE-VR4 Ethernet/InfiniBand
- 4x 200GBASE-VR2 Ethernet/InfiniBand
- 8x 100GBASE-VR1 Ethernet

Standards:

- OSFP MSA
- CMIS
- IEEE 802.3db/802.3ck
- RoHS
- Class 1 Laser

General Specifications:

Parameter	Min	Typical	Max	Unit	Note
Operating Temperature	25	-	70	°C	
Operating Humidity	5	-	85	%	
Power Consumption	14	-	16	W	
Power Supply Voltage	3.135	3.3	3.465	V	
Transmission Distance	-	-	50	m	
Data Rate (Total)	-	850	-	Gbps	1
Signaling Rate per Lane	-	53.125	-	GBd	2

Notes:

1 - Total aggregate bit rate

2 - Per lane electrical signalling rate with PAM4 modulation

PRE-O800-IB-VR8

OSFP800, VR8, 850nm, 800GE/InfiniBand, 50m,
MMF/MPO16-APC, C-Temp, DDM



Optical Characteristics: Transmitter

Parameter	Min	Typical	Max	Unit
Wavelength	840	850	948	nm
Average Launch Power, per lane	-4.6	-	4	dBm
Extinction Ratio	2.5	-	-	dB
Transmitter and Dispersion Eye Closure, per Lane	-	-	4.4	dBm
Optical Return Loss Tolerance	-	-	14	dB
Transmitter OFF Output Power, per lane	-	-	-30	dBm

Optical Characteristics: Receiver

Parameter	Min	Typical	Max	Unit
Wavelength	840	850	948	nm
Damage Threshold, per lane	5	-	-	dBm
Average Receive Power, per lane	-6.3	-	4	dBm
Stressed Receiver Sensitivity, per lane	-	-	-1.8	dBm
Receiver Reflectance	-	-	-15	dB

Product Ordering Information

Part Number	Description
PRE-O800-IB-VR8	OSFP800, VR8, 850nm, 800GE/InfiniBand, 50m, MMF/MPO16-APC, C-Temp, DDM

r1_05202026