

PRE-OR400-4-IB-VR4

OSFP-RHS, VR4, 850nm, 400GE/InfiniBand, 50m, MMF, MPO12, C-Temp



Product Features:

- OSFP-RHS Form Factor
- VCSEL Transmitters
- PIN Receivers
- 50m Reach over MMF
- MPO-12/APC Optical Connector
- < 8W Power Consumption
- Commercial Temperature Rated
- Digital Diagnostic Monitoring (DDM)



Product Applications:

- 1x400G Ethernet/InfiniBand
- 2x200G Ethernet/InfiniBand
- 4x100G Ethernet

Standards:

- CMIS
- OSFP MSA
- IEEE 802.3db & 802.3ck
- RoHS
- Class 1 Laser

General Specifications:

Parameter	Min	Typical	Max	Unit	Note
Operating Temperature	0	-	70	°C	
Operating Humidity	5	-	85	%	
Power Consumption	-	-	8	W	
Power Supply Voltage	3.135	3.3	3.465	V	
Transmission Distance	-	-	50	m	
Data Rate (Total)	-	425	-	Gbps	1
Signaling Rate per Lane	-	53.125	-	GBd	2

Notes:

1 - Total aggregate bit rate

2 - Per lane electrical signalling rate with PAM4 modulation

PRE-OR400-4-IB-VR4

OSFP-RHS, VR4, 850nm, 400GE/InfiniBand, 50m, MMF, MPO12, C-Temp



Optical Characteristics: Transmitter

Parameter	Min	Typical	Max	Unit
Wavelength	842	850	868	nm
Average Launch Power, per lane	-4.6	-	4	dBm
Transmitter OFF Output Power, per lane	-	-	-30	dBm
Transmitter and Dispersion Eye Closure for PAM4, per lane	-	-	4.4	dBm
RMS Spectral Width	-	-	0.65	dB
Extinction Ratio	2.5	-	-	dB

Optical Characteristics: Receiver

Parameter	Min	Typical	Max	Unit
Wavelength	842	-	870	nm
Damage Threshold, per lane	5	-	-	dBm
Average Receive Power, per lane	-6.3	-	4	dBm
Stressed Receiver Sensitivity, per lane	-	-	-1.8	dBm
Receiver Reflectance	-	-	-15	dB

Product Ordering Information

Part Number	Description
PRE-OR400-4-IB-VR4	OSFP-RHS, VR4, 850nm, 400GE/InfiniBand, 50m, MMF, MPO12, C-Temp

r2_03122026