

# PRE-QD800-2VR4

QSFP-DD800, 2x400G-VR4, 850nm, 800G, 50m,  
MMF/Dual MPO12-APC, C-Temp



## Product Features:

- VCSEL Transmitters
- PIN Receivers
- 50m Reach over MMF
- Dual MPO-12/APC Optical Connector
- < 16W Power Consumption
- Commercial Temperature Rated
- Digital Diagnostic Monitoring (DDM)



## Product Applications:

- 800GBASE-VR8 Ethernet
- 2x 400GBASE-VR4 Ethernet
- 4x 200GBASE-VR2 Ethernet
- 8x 100GBASE-VR1 Ethernet

## Standards:

- QSFP-DD MSA
- CMIS
- IEEE Std 802.3df-2024
- RoHS
- Class 1 Laser

## General Specifications:

Parameter	Min	Typical	Max	Unit	Note
Operating Temperature	0	-	70	°C	
Operating Humidity	5	-	85	%	
Power Consumption	-	-	16	W	
Power Supply Voltage	3.135	3.3	3.465	V	
Transmission Distance	-	-	50	m	
Data Rate (Total)	-	850	-	Gbps	1
Signaling Rate per lane	-	53.125	-	GBd	2

Notes:

1 - Total aggregate bit rate

2 - Per lane electrical signalling rate with PAM4 modulation

# PRE-QD800-2VR4

QSFP-DD800, 2x400G-VR4, 850nm, 800G, 50m,  
MMF/Dual MPO12-APC, C-Temp



## Optical Characteristics: Transmitter

Parameter	Min	Typical	Max	Unit
Wavelength	842	850	870	nm
Average Launch Power, per lane	-4.6	-	4	dBm
Transmitter OFF Output Power, per lane	-	-	-30	dBm
Transmitter and Dispersion Eye Closure for PAM4, per lane	-	-	4.4	dBm
Optical Return Loss Tolerance	-	-	14	dB
RMS Spectral Width	-	-	0.65	dB
Extinction Ratio	2.5	-	-	dB

## Optical Characteristics: Receiver

Parameter	Min	Typical	Max	Unit
Wavelength	840	-	870	nm
Damage Threshold, per lane	5	-	-	dBm
Average Receive Power, per lane	-6.3	-	4	dBm
Stressed Receiver Sensitivity, per lane	-	-	-1.8	dBm
Receiver Reflectance	-	-	-15	dB

## Product Ordering Information

Part Number	Description
PRE-QD800-2VR4	QSFP-DD800, 2x400G-VR4, 850nm, 800G, 50m, MMF/Dual MPO12-APC, C-Temp

r2\_03122026