

PRE-QSFP56DD-ZRPHT

QSFP-DD, OpenZR+, 0dBm, Tunable, C-Band, 400G,
80km (unamplified)



Product Features:

- Full DWDM C-band Tunable
- Digital Coherent Optics
- Up to +1dBm TX Power
- 1000km+ Reach (Amplified)
- 80km Reach (Unamplified)
- Duplex LC-UPC Connector
- C-Temp
- <23.5W Power Consumption
- Digital Diagnostics Monitoring (DDM) and Versatile Diagnostics Monitor (VDM)



Product Applications:

- Data Center Interconnect
- ROADM and Long Haul Networks
- DWDM 400G Ethernet

Compliance:

- QSFP-DD
- OpenZR+ and OIF 400ZR
- CMIS and C-CMIS
- RoHS

General Specifications:

Parameter	Min	Typical	Max	Unit
Case Operating Temperature	0	-	70	°C
Power Consumption	-	-	23.5 ¹	W
Power Supply Voltage	3.14	3.3	3.46	V
Operating Humidity	5	-	95	%
Storage Temperature	-40	-	85	°C
Transmission Distance (PtP)	-	-	80 ²	km
Transmission Distance (OLS)	-	-	1000 ³	km
Data Rate (Total)	100	-	481	Gbps

1 The actual Power Consumption will vary depending on the application selected.

2 Unamplified, Single Wave Point to Point

3 Line System, dispersion limited links, G.652 fiber. Max reach will depend on network design and application configured.



www.belden.com

These products may be protected by one or more patents. For further information, please contact our product support team.

2245 Brighton-Henrietta Town Line Road
Rochester, New York 14623 | [Technical Support](#)
+1 (855) 505-6324 • +1 (585) 500-4090



www.precisionot.com

PRE-QSFP56DD-ZRPHT

QSFP-DD, OpenZR+, 0dBm, Tunable, C-Band, 400G, 80km
(unamplified)



Applications

HOST				MEDIA				
Host IF	FEC	Modulation	Baud Rate (GBd)	Line Rate	Mode	FEC	Modulation	Baud Rate (GBd)
1x 400GAUI-8	RS(544,514)	PAM4	26.5625	400G	400ZR	C-FEC	DP-16QAM	59.8438
4x 100GAUI-2	RS(544,514)	PAM4	26.5625	400G	400ZR	C-FEC	DP-16QAM	59.8438
1x 400GAUI-8	RS(544,514)	PAM4	26.5625	400G	ZR400-OFEC-16QAM	O-FEC	DP-16QAM	60.1385
4x 100GAUI-2	RS(544,514)	PAM4	26.5625	400G	ZR400-OFEC-16QAM	O-FEC	DP-16QAM	60.1385
3x 100GAUI-2	RS(544,514)	PAM4	26.5625	300G	ZR300-OFEC-8QAM	O-FEC	DP-8QAM	60.1385
2x 100GAUI-2	RS(544,514)	PAM4	26.5625	200G	ZR200-OFEC-QPSK	O-FEC	DP-QPSK	60.1385
1x 100GAUI-2	RS(544,514)	PAM4	26.5625	100G	ZR100-OFEC-QPSK	O-FEC	DP-QPSK	30.0693

Optical Characteristics: Transmitter

Parameter	Min	Typical	Max	Unit
Tx Output Power Range	-6	-	1	dBm
Tx Output Power Resolution	-	-	0.1	dB
Tx Output Power Accuracy	-1	-	1	dB
Tx Output Power Stability	-1	-	1	dB
In-band OSNR	38	-	-	dB
Out-of-Band OSNR	40	-	-	dB
Tx Disable Power	-	-	-20	dBm
Tx Reflectance	-	-	-20	dB
Frequency Range	191.3	-	196.1	THz
Frequency Fine Tuning	3.125	-	100	GHz

PRE-QSFP56DD-ZRPHT

QSFP-DD, OpenZR+, 0dBm, Tunable, C-Band, 400G, 80km (unamplified)



Optical Characteristics: Receiver

Parameter		Min	Typical	Max	Unit
Rx Input Power (Unamplified OSNR>35dB)	400ZR	-20	-	0	dBm
	ZR400-OFEC-16QAM	-22		0	
	ZR300-OFEC-8QAM	-26		0	
	ZR200-OFEC-QPSK	-30		0	
	ZR100-OFEC-QPSK	-32		0	
Rx Input Power (Amplified)	400ZR	-12	-	0	dBm
	ZR400-OFEC-16QAM	-12		0	
	ZR300-OFEC-8QAM	-15		0	
	ZR200-OFEC-QPSK	-18		0	
	ZR100-OFEC-QPSK	-18		0	
Rx OSNR Tolerance	400ZR	-	-	26	dB/0.1nm
	ZR400-OFEC-16QAM			24	
	ZR300-OFEC-8QAM			21	
	ZR200-OFEC-QPSK			16	
	ZR100-OFEC-QPSK			12.5	
CD Tolerance	400ZR	-	-	2,400	ps/nm
	ZR400-OFEC-16QAM			20,000	
	ZR300-OFEC-8QAM			40,000	
	ZR200-OFEC-QPSK			50,000	
	ZR100-OFEC-QPSK			100,000	

Product Ordering Information

Part Number	Description
PRE-QSFP56DD-ZRPHT	QSFP-DD, OpenZR+, 0dBm, Tunable, C-Band, 400G, 80km (unamplified), SMF/LC, C-Temp

r1_02242026