

PRE-QSFP56DD-ZRX4T

QSFP-DD, ZR+, -7 to +4dBm, Tunable, C-Band, 400G, 120km (unamplified)



Product Features:

- Full DWDM C-band Tunable
- -7 to +4dBm TX Power
- 1000km+ Reach (Amplified)
- 120km Reach (Unamplified)
- Duplex LC-UPC Connector
- C-Temp
- <19W Power Consumption
- Digital Diagnostics Monitoring (DDM)



Product Applications:

- Data Center Interconnect
- ROADM and Long Haul Networks
- DWDM 400G Ethernet/FlexO

Standards:

- QSFP-DD
- CMIS and C-CMIS
- RoHS

General Specifications:

Parameter	Min	Typical	Max	Unit
Case Operating Temperature	0	-	75	°C
Power Consumption	-	-	18.8	W
Power Supply Voltage	3.14	3.3	3.46	V
Operating Humidity	5	-	95	%
Storage Temperature	-40	-	85	°C
Transmission Distance	-	-	1000 ¹	km
Data Rate (Total)	200	-	505.11	Gbps

1 - Line System, dispersion limited links, G.652 fiber. Max reach will depend on network design.

PRE-QSFP56DD-ZRX4T

QSFP-DD, ZR+, -7 to +4dBm, Tunable, C-Band, 400G, 120km (unamplified)



Applications²:

Host				Media			
Host IF	FEC	Modulation	Baud Rate	Mode	FEC	Modulation	Baud Rate
400GAUI-8	RS(544,514)	PAM4	26.5625 GBd	400ZR	C-FEC	DP-16QAM	59.8438 GBd
100GAUI-2	RS(544,514)	PAM4	26.5625 GBd	400ZR	C-FEC	DP-16QAM	59.8438 GBd
400GAUI-8	RS(544,514)	PAM4	26.5625 GBd	ZR400-OFEC-16QAM	O-FEC	DP-16QAM	60.1385 GBd
100GAUI-2	RS(544,514)	PAM4	26.5625 GBd	ZR400-OFEC-16QAM	O-FEC	DP-16QAM	60.1385 GBd
400GAUI-8	RS(544,514)	PAM4	26.5625 GBd	FLEXO-4-DO-16QAM	O-FEC	DP-16QAM	63.1395 GBd
100GAUI-2	RS(544,514)	PAM4	26.5625 GBd	FLEXO-4-DO-16QAM	O-FEC	DP-16QAM	63.1395 GBd

2 - A shortened version of all the applications this module supports is shown here. Only non-muxponder 400G modes are interoperable with other modules using the same application. For the full supported list please reach out to your direct Sales/SE representative.

Optical Characteristics: Transmitter

Parameter	Min	Typical	Max	Unit
Tx Output Power Range	-7	-	4	dBm
Tx Output Power Resolution	-	-	0.1	dB
Tx Output Power Accuracy	-1	-	1	dB
Tx Output Power Stability	-1	-	1	dB
In-band OSNR	37	-	-	dB
Out-of-Band OSNR	45	-	-	dB
Tx Disable Power	-	-	-20	dBm
Tx Reflectance	-	-	-27	dBm
Frequency Range	191.25	-	196.125	THz
Frequency Fine Tuning	5	-	100	GHz

PRE-QSFP56DD-ZRX4T

QSFP-DD, ZR+, -7 to +4dBm, Tunable, C-Band, 400G, 120km (unamplified)



Optical Characteristics: Receiver

Parameter		Min	Typical	Max	Unit
Rx Input Power (Unamplified OSNR>35dB)	400ZR	-21	-	5	dBm
	ZR400-OFEC-16QAM	-22		5	
	FLEXO-4-DO-16QAM	-21		5	
Rx Input Power (Amplified)	400ZR	-12	-	-7	dBm
	ZR400-OFEC-16QAM	-12		-7	
	FLEXO-4-DO-16QAM	-12		-7	
Rx OSNR Tolerance	400ZR	-	-	24.8	dB/0.1nm
	ZR400-OFEC-16QAM	-		21.9	
	FLEXO-4-DO-16QAM	-		22.4	
CD Tolerance	400ZR	-2400	-	2400	ps/nm
	ZR400-OFEC-16QAM	-81000		81000	
	FLEXO-4-DO-16QAM	-73500		73500	

Product Ordering Information

Part Number	Description
PRE-QSFP56DD-ZRX4T	QSFP-DD, ZR+, -7 to +4dBm, Tunable, C-Band, 400G, 120km (unamplified), SMF/LC, C-Temp

r1_10202025