

PRE-SFP-SX, PRE-SFP-SXI
SFP, 850nm, MMF, 550m, 1.25 Gbps



Product Features:

- VCSEL Transmitter
- PIN Receiver
- MMF Transmission Medium
- LC-UPC Connector Type
- Digital Diagnostic Monitoring
- C-Temp and I-Temp Available



Product Applications:

- 1G Ethernet
- Fiber Channel

General Specifications

Parameter	Symbol	Min	Typ	Max	Unit
Case Operating Temperature (Commercial)	T_{op}	0	-	70	°C
Case Operating Temperature (Industrial)	T_{op}	-40	-	85	°C
Power Consumption	P_w	-	-	1	W
Power Supply Current	I_{cc}	-	-	280	mA
Power Supply Voltage	V_{cc}	-0.5	-	4	V
Storage Humidity	H_s	5	-	95	%
Storage Temperature	T_s	-40	-	85	°C
Transmission Distance (OM2)	TD	-	-	550	m
Data Rate (Total)	DR_T	-	-	1.25	Gbps

Optical Characteristics: Transmitter

Parameter	Symbol	Min	Typ	Max	Unit
Center Wavelength	λ_c	830	850	860	nm
Transmit Power	P_{OUT}	-9	-	-3	dBm
Spectral Width	σ	-	-	0.85	nm
Side Mode Suppression Ratio	SMSR	30	-	-	dB
Dispersion Penalty	DP	-	-	3	dB
Extinction Ratio	ER	9	-	-	dB
Relative Intensity Noise	RIN	90	100	110	dB/Hz
Transmitter OFF Output Power	P_{OFF}	-	-	-45	dB

Optical Characteristics: Receiver

Parameter	Symbol	Min	Typ	Max	Unit
Receiver Wavelength	λ_r	770	850	860	nm
Damage Threshold	P_D	5	-	-	dBm
Input Saturation Power	P_{SAT}	0	-	-	dBm
Receiver Sensitivity	R	-	-	-17	dBm
LOS Assert	LOS_A	-35	-	-	dBm
LOS De-Assert	LOS_D	-	-	-18	dBm
LOS Hysteresis	LOS_H	0.5	2	6	dB

Product Ordering Information

Part Number	Description
PRE-SFP-SX	SFP, 850nm, MMF, 550m, 1.25 Gbps, C-Temp
PRE-SFP-SXI	SFP, 850nm, MMF, 550m, 1.25 Gbps, I-Temp