

PRE-SFP10G-Dxx-40, PRE-SFP10G-Dxx-40I
 SFP+, DWDM 100GHz, ITU 17-61, SMF, 40km, 10Gbps



Product Features:

- EML Transmitter
- PIN Receiver
- 100GHz DWDM Grid
- SMF Transmission Medium
- LC-UPC Connector Type
- Digital Diagnostics Monitoring (DDM)
- C-Temp and I-Temp Available
- Supports Bit Rates up to 11.3Gbps



Product Applications:

- 10G Ethernet
- CPRI
- Fiber Channel

General Specifications

Parameter	Symbol	Min	Typ	Max	Unit
Case Operating Temperature (Commercial)	T_{op}	0	-	70	°C
Case Operating Temperature (Industrial)	T_{op}	-40	-	85	°C
Power Consumption	P_w	-	-	1.4	W
Power Consumption (I-Temp)	P_w	-	-	1.6	W
Power Supply Current	I_{cc}	-	-	490	mA
Power Supply Voltage	V_{cc}	3.14	3.3	3.46	V
Storage Humidity	H_s	5	-	95	%
Storage Temperature	T_s	-40	-	85	°C
Transmission Distance	TD	-	-	40	km
Data Rate (Total)	DR_T	-	10.3125	11.3	Gbps

Optical Characteristics: Transmitter

Parameter	Symbol	Min	Typ	Max	Unit
Center Wavelength	λ_c	$\lambda_c - 0.05$	-	$\lambda_c + 0.05$	nm
Transmit Power	P_{OUT}	-1	-	3	dBm
Spectral Width	σ	-	-	1	nm
Side Mode Suppression Ratio	SMSR	30	-	-	dB
Dispersion Penalty	DP	-	-	2	dB
Extinction Ratio	ER	8.2	-	-	dB
Transmitter OFF Output Power	P_{OFF}	-	-	-30	dBm

Optical Characteristics: Receiver

Parameter	Symbol	Min	Typ	Max	Unit
Receiver Wavelength	λ_r	1270	-	1610	nm
Input Saturation Power	P_{SAT}	0	-	-	dBm
Receiver Sensitivity	R	-	-	-16	dBm
LOS Assert	LOS_A	-30	-	-	dBm
LOS De-Assert	LOS_D	-	-	-17	dBm
LOS Hysteresis	LOS_H	0.5	-	-	dB

Product Ordering Information

Part Number	Description
PRE-SFP10G-Dxx-40	SFP+, DWDM 100GHz, ITU 17-61, SMF, 40km, 10Gbps, C-Temp
PRE-SFP10G-Dxx-40I	SFP+, DWDM 100GHz, ITU 17-61, SMF, 40km, 10Gbps, I-Temp