

PRE-XFP-Bxx-80, PRE-XFP-Bxx-80I

XFP, 1490nm/1550nm, BIDI, SMF, 80km, 10Gbps

Product Features:

- 1490 or 1550nm EML Transmitter
- APD Receiver
- SMF Transmission Medium
- LC-UPC Connector Type
- Digital Diagnostics Monitoring (DDM)
- C-Temp and I-Temp Available
- Supports Bit Rates up to 11.3Gbps
- <2.5W Power Dissipation



Product Applications:

- 10G Ethernet
- SONET SDH
- OTN Transport

General Specifications

Parameter	Symbol	Min	Typ	Max	Unit
Case Operating Temperature (Commercial)	T _{op}	-10	-	70	°C
Case Operating Temperature (Industrial)	T _{op}	-40	-	85	°C
Power Supply Voltage	V _{cc}	3.14	3.3	3.47	V
Power Supply Current	I _{cc}	-	-	650	mA
Storage Humidity	H _s	5	-	95	%
Storage Temperature	T _s	-40	-	85	°C
Transmission Distance	TD	-	-	80	km
Data Rate (Total)	DR _T	9.95	10.3125	11.3	Gbps

PRE-XFP-Bxx-80, PRE-XFP-Bxx-80I

XFP, 1490nm/1550nm, BIDI, SMF, 80km, 10Gbps



Optical Characteristics: Transmitter

Parameter	Symbol	Min	Typ	Max	Unit
Center Wavelength (B45)	λ_c	1480	1490	1500	nm
Center Wavelength (B54)	λ_c	1540	1550	1560	nm
Transmit Power (B45)	P _{OUT}	0	-	4	dBm
Transmit Power (B54)	P _{OUT}	-1	-	3	dBm
Spectral Width	σ	-	-	1	nm
Side Mode Suppression Ratio	SMSR	30	-	-	dB
Extinction Ratio	ER	6	-	-	dB
Transmitter OFF Output Power	P _{OFF}	-	-	-45	dB

Optical Characteristics: Receiver

Parameter	Symbol	Min	Typ	Max	Unit
Receiver Wavelength (B45)	λ_r	1540	1550	1560	nm
Receiver Wavelength (B54)	λ_r	1480	1490	1500	nm
Input Saturation Power	P _{SAT}	-6	-	-	dBm
Receiver Sensitivity	R	-	-	-24	dBm
LOS Assert	LOS _A	-38	-	-	dBm
LOS De-Assert	LOS _D	-	-	-25	dBm
LOS Hysteresis	LOS _H	0.5	-	4	dB

Product Ordering Information

Part Number	Description
PRE-XFP-B45-80	SFP+, 1490nm Tx/1550nm Rx, BIDI, SMF, 80km, 10Gbps, C-Temp
PRE-XFP-B45-80I	SFP+, 1490nm Tx/1550nm Rx, BIDI, SMF, 80km, 10Gbps, I-Temp
PRE-XFP-B54-80	SFP+, 1550nm Tx/1490nm Rx, BIDI, SMF, 80km, 10Gbps, C-Temp
PRE-XFP-B54-80I	SFP+, 1550nm Tx/1490nm Rx, BIDI, SMF, 80km, 10Gbps, I-Temp